## Decals & Floor Graphics

## How to Apply Decals/Floor Graphics

Our decals and floor graphics can be applied on flat and slightly curved surfaces. We recommend applying them in the steps indicated below.




- Before applying the decal, clean the application surface of any oil or dirt, and ensure that it is dry.
- Test out a small piece of decal material on your application surface before applying the main product. If you intend to remove the vinyl later, test out removability on your surface as well. If the result is satisfactory, proceed to the next step.
- Peel a corner, or the edge, of the decal away from the backing and apply it to the surface.
- Gradually peel more of the decal and apply it a little at a time to the surface.
- Work your way through the entire decal.
- If you have any large bubbles, you can eliminate them by carefully heating the area with a hairdryer very briefly, puncturing them with a needle, and applying pressure with your thumb.

  Smaller bubbles will naturally disappear over time.

## How to Remove Decals/Floor Graphics

Our 4mil removable vinyl can be removed within 6 month depending on the substrate it is applied to. Our 13mil removable vinyl can be removed within 2 years under normal indoor conditions. We recommend removing the decals by following steps indicated below.



- 1 Start with a small section of the decal. Use a hairdryer on a low temperature setting to warm up the decal slightly. Test the temperature of the decal with your hand to make sure it does not get too hot.
- Peel back the corner of the decal at 180 degrees.

  If you are having difficulty, warm the section some more with the hairdryer.
- Slowly peel the decal little by little, applying heat when needed.
- Once the decal has been removed, wipe any remaining residue from the surface.